


3ARW0-0BL

Industrial Grade



Cover

Top Color	Black
Thickness	
Material	PU Impregnation
Pattern	N/A
Durometer	

Carcass

Plies	3
Fabric	Polyester
Anti-static	Yes
Laterally Rigid	Yes
Pulley Side Material	Polyester Whisper

Weight

0.055 lbs./in.-ft. (3.2 kg/m²)

Maximum Width

118" (3m)

Overall Thickness

0.105" (2.7mm)

Minimum Pulley at 70°F

Min Pulley <180°	3" (76.2mm)
Min Pulley Reverse Bend	3" (76.2mm)

Contact Temperature Range

5°F to 210°F (-15°C to 99°C)

Intermittent Contact Mol Belting

Working Tension

Minimum	29-46 lbs./in. (5.1-8.1 N/mm)
Maximum	135 lbs./in. (23.6 N/mm)

Elongation

0.4% @ 29 lbs./in. (5.1 N/mm)
 0.7% @ 46 lbs./in. (8.1 N/mm)
 2% @ 135 lbs./in. (23.6 N/mm)

Coefficient of Friction

Mild Steel	0.25
S/S	0.27
UHMW	0.2

Splicing/Lacing Methods

Splicing	
Lacing #1	Unibar #1 SP
Lacing #2	Alligator #1

Characteristics

FDA	No
Non-Marking	Yes
Flame Retardant	No
Release Characteristics	Good
Incline Conveying	No
Trough Conveying	No
Swan Neck Conveying	Good
Metal Detectors (Dependent on Sensitivity)	Contact Mol Belting
Chemical Resistance	See Chart

Accessories

Edgecap	No
Guide	Yes
Cleats	No
Sidewall	No
Profile	No