


TUBS-1

Thermoking



Cover

Top Color	Blue
Thickness	
Material	TPU
Pattern	Satin
Durometer	48 D

Carcass

Plies	0
Fabric	
Anti-static	No
Laterally Rigid	No
Pulley Side Material	TPU

Weight

0.018 lbs./in.-ft. (1.1 kg/m²)

Maximum Width

23.625" (0.6m)

Overall Thickness

0.04" (1mm)

Minimum Pulley at 70°F

Min Pulley <180°	0.375" (9.5mm)
Min Pulley Reverse Bend	0.625" (15.9mm)

Contact Temperature Range

-22°F to 140°F (-30°C to 60°C)

Intermittent	Contact Mol Belting
--------------	---------------------

Working Tension

Minimum	4.6-7.6 lbs./in. (0.8-1.3 N/mm)
Maximum	11.4 lbs./in. (2 N/mm)

Elongation

2% @ 4.6 lbs./in. (0.8 N/mm)
4% @ 7.6 lbs./in. (1.3 N/mm)
8% @ 11.4 lbs./in. (2 N/mm)

Coefficient of Friction

Mild Steel	0.4
S/S	0.42
UHMW	0.35

Splicing/Lacing Methods

Splicing	Finger Splice
Lacing #1	
Lacing #2	

Characteristics

FDA	Yes
USDA Dairy	Yes
USDA Meat And Poultry	Yes
Non-Marking	Yes
Flame Retardant	No
Release Characteristics	Good
Incline Conveying	No
Trough Conveying	Yes
Swan Neck Conveying	Poor
Metal Detectors	Contact Mol Belting
(Dependent on Sensitivity)	
Chemical Resistance	See Chart

Accessories

Edgecap	No
Guide	Yes
Cleats	No
Sidewall	No
Profile	No